Marking Tubes, Labels and more!





LETATVIN

LM-550A/PC

Professional choice for your cable marking job!



- Our fastest printing speed ever!
- ◆Versatile printing capability! (Tube \$\phi\$1.5~8.0mm)
- Connect to your PC with a USB cable or a USB flash drive.

Comes with plastic carry case






DEVELOPED FOR MAXIMIZING CABLE MARKING JOB PRODUCTIVITY

Long consumable roll length

LM-550A/PC adopts the dedicated consumables which have a longer roll length. Long roll length saves reloading time.



^{*}LM-TP5xxT (Transparent) and TP5xxY (Yellow) remain as 8meters,

High-speed marking


LM-550A/PC has an enhanced feeding system that provides you with marking speed at 40mm/second, LM-550A/PC can make approx 52pcs of 20mm-length tube per minute.

For marking on Tube	LM-550A	88 Saving time
	MAX previous model	
	LM-390A	100
- 1	Marking tin	ne

Maximum 250,000 characters built-in large memory storage

Easy access from your PC with USB

LM-550A/PC features a USB port for a direct cable connection with a WindowsPC (for direct printing or file transfers), and a USB flash drive slot for transferring computer files made in our dedicated "LETATWIN PC EDITOR" software.



SPECIFICATIONS

ITEMS	CONTENTS	
Name	MAX ELECTRONIC LETTERING MACHINE LM-550A/PC	
Dimensions	295 (W)×293 (D)×94 (H) mm	
Weight	2.4kg	
Printing method	Thermal transfer method (300dpi)	
Display	LCD dot matrix: 64×160 Pixel (Backlit)	
Printing speed	40mm/s (Standard) 20mm/s (Low temperature mode)	
Maximum Printing length	Tube : 20m, Tape : 5m By multiple copy printing,maximum 30copies, upto Tube ; 100m, Tape ; 7m	
Maximum number of characters to input	5,000 characters per file	
Character size	1.3,2,3,4,6mm height	
Usable tube	Φ1.5mm ~ 8.0mm (PVC tube) (For Φ1.5~2.0mm tubes, the dedicated attachment (standard accessory) is required.) Φ2.0mm ~ 6.5mm (Heat Shrinkable tube)	
Usable tape	Width 5, 9, 12mm (Max genuine tape)	
Tube cutting method	Auto half cut, manual full cut	
Internal memory	250,000 characters (Maximum 50 files)	
External memory	USB memory	
Interface	USB 2.0 full speed	
Power supply	DC12V, 3.0A Use only specified AC Adapter (100V~240V)	
Power consumption	Max 30W	
Operating environment	10°C to 35°C	

Versatile marking capability

Various marking media and sizes

- Φ1.5~Φ8.0mm PVC tubes
- 5mm/9mm/12mm wide MAX dedicated tapes



I.D. plates

Oval tubes *For the availability of European style marking media, please contact our distributor.

To optimize printing quality,

multiple combinations of settings (such as vertical/ horizontal print positions and print density) can be saved to support European style marking media etc.

Large and backlit LCD display

Backlit LCD display makes your confirmation of input contents easy, even if you work in a dim jobsite.



⊬+ φ1.5mm

■ The pitch can be set up to maximum 60mm.

Marking on tape: 4 up to 60mm

Marking on tube: 10 up to 60mm "(Auto pitch function is available for more than 60mm)"



Economical refill-type ink ribbon.









LM-TU336N2 WHITE \$\phi_3.6mm\times 100m/ROLL\$ LM-TU342N2 WHITE \$\phi 4.2mm \times 80m/ROLL\$

INK RIBBON CASE LM-RC500



ECONOMICAL INK RIBBON REFILLS 10 ROLLS/BOX LM-IR50B (BLACK) 110m/ROLL

MAX HIGH QUALITY TUBE 1ROLL/BOX		
LM-TU432L WHITE	Φ3.2mm×200m/R0LL	
LM-TU436L WHITE	Ø3.6mm×200m/ROLL	
	Ф 4.2mm×200m/R0LL	
LM-TU452L WHITE	Ф 5.2mm×135m/R0LL	
LM-TU464L WHITE	Ø 6.4mm×100m/ROLL	

INK RIBBON REFILLS FOR HEAT SHRINKABLE TUBE 10 ROLLS/BOX

LM-IR50BP (BLACK)	110m/ROLL
LM-IR50W (WHITE)	70m/ROLL

TAPE CASSETTE 10PCS./BOX				
LM-TP505W (WHITE)	5mm(W) × 16m(L)/PC			
LM-TP505Y (YELLOW)	5mm(W) × 8m(L)/PC			
LM-TP505T (TRANSPARENT)	5mm(W) × 8m(L)/PC			
LM-TP509W (WHITE)	$9mm(W) \times 16m(L)/PC$			
LM-TP509Y (YELLOW)	9mm(W) × 8m(L)/PC			
LM-TP509T (TRANSPARENT)	9mm(W) × 8m(L)/PC			
LM-TP512W (WHITE)	$12mm(W) \times 16m(L)/PC$			
LM-TP512Y (YELLOW)	12mm(W) × 8m(L)/PC			



PC REQUIREMENTS For Windows 10 / 8.1 / 8 / 7 operating systems. Windows® is a registered trademark of Microsoft Corporation (US) in U.S.A. or other countries.

The specifications and design of the products in this catalogue will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.

