



Label Rewinder

- All Steel Construction
- Automatic Speed Control
- Inside / Outside Rewinding
- 8 Inch OD Capacity
- Supports Three Core Sizes

Features



Core Adapters



Rotating Direction Switch



Steel Construction



LR-1000



ISO 9001:2000 CERTIFIED

GODEX

LR-1000

Product Specifications

Model	LR-1000
Label Width	1" (25.4 mm) - 4.72" (120 mm)
Label Roll Weight	Max. 8.8 lbs (4Kg)
Rewind Speed	Up to 12 IPS (304.8 mm/s) with 3" core Rewind speed depending on core diameter
Label Roll Diameter	Max. O.D. 6" (152.4 mm) for label inside Max. O.D. 8" (203.2 mm) for label outside
Core Diameter	I.D. 1" (24.4 - 26.4 mm) I.D. 1.5" (37.1 - 39.1 mm) I.D. 3" (75.2 - 77.2 mm)
Direction	Label inside / Label outside
Power	AC 120V or AC 230V (Factory options)
Environment	Operation temperature: 41°F to 104°F (5°C to 40°C) Storage temperature: -4°F to 122°F (-20°C to 50°C)
Humidity	Operation: 30-85%, non-condensing. Storage: 10-90%, non-condensing.
Agency Approvals	CE, FCC Class A
Dimension	Length: 11.8" (300 mm) Height: 12.1" (308 mm) Width: 8.7" (220 mm)
Weight	13.2 lbs (6Kg), excluding consumables
Rewind End Detection	Label inside: O.D. 6" (152.4 mm) Label outside: O.D. 8" (203.2 mm)

*Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.



LAAB
aa@laab.com.tw
+886-2-2389-0101

Godex China
infoGC@godexintl.com
+86-21-5665-1313

Godex Europe
infoGE@godexintl.com
+49-2193-53396-0

Godex Americas
infoGA@godexintl.com
+1-805-987-5100